

FLOPPYGUARD SQ™ (Squarelocked) is Hose Master's line of squarelocked stripwound hose. It can be used in a wide variety of applications where the added flexibility of squarelocked hose is required. It is used as shielding on electrical wiring and fiber optic cable. FloppyGuard SQ™ is available in sizes ranging from 5/32" - 1/2" ID.



FLOPPYGUARD SQ™ Features

- Flexibility
- Abrasion-resistant
- Crush-resistant
- Chemical-resistant
- Ultrasonically cleaned

FLOPPYGUARD SQ™ Applications

- Flexible, durable guard for wire, cable, or tubing
- Fiber optic cables
- Internal and external protection of other hoses

FLOPPYGUARD SQ™ (Squarelocked)

FLOPPYGUARD SQ™ is made from T304 stainless steel .010 thick.

FLOPPYGUARD SQ™ (Squarelocked) Hose Specifications

Nominal Inside Diameter (in.)	Part Number	Minimum Bend Radius (in.)	Weight Per Foot (lbs.)
5/32	SQ10SS0015	0.6	0.03
3/16	SQ10SS0018	0.7	0.04
7/32	SQ10SS0021	0.8	0.04
1/4	SQ10SS0025	0.9	0.05
9/32	SQ10SS0038	0.9	0.05
5/16	SQ10SS0031	1.1	0.06
11/32	SQ10SS0034	1.1	0.06
3/8	SQ10SS0037	1.1	0.06
13/32	SQ10SS0040	1.2	0.07
7/16	SQ10SS0043	1.2	0.08
15/32	SQ10SS0047	1.2	0.08
1/2	SQ10SS0050	1.3	0.09

* Other material gauges may be available. Please consult factory.