



FLOPPYGUARD™ (Floppy Interlocked)

FLOPPYGUARD™ (Interlocked) is Hose Master's line of floppy interlocked metal hose. Constructed from T304 or T316 stainless steel, this product offers flexibility, strength, durability, and crush resistance. FloppyGuard™ is available in sizes from 3/16" - 12" ID.



FLOPPYGUARD™ Features

- Flexibility
- Abrasion-resistant
- Crush-resistant
- Chemical-resistant
- Ultrasonically cleaned (up to 2" ID)

FLOPPYGUARD™ Applications

- Flexible, durable guard for wire, cable, or tubing
- Casing for fiber optic cables
- Internal and external protection of other hoses
- Air and fume handling, exhaust ducting, and dust collection systems

FLOPPYGUARD™ (Interlocked) Part Numbers SBxx [Material](#) xxxx

[Material Codes](#)

SS - T304 Stainless Steel
16 - T316 Stainless Steel
GS - Galvanized Steel*

FLOPPYGUARD™ (Interlocked) Hose Specifications

Nominal Inside Diameter (in.)	Part Number	Standard Material Thickness**	Minimum Bend Radius (in.)	Weight Per Foot (lbs.)
3/16	SB08_0018	.008	1.1	0.05
1/4	SB08_0025	.008	1.4	0.05
5/16	SB08_0031	.008	1.7	0.06
3/8	SB10_0037	.010	2.2	0.11
7/16	SB10_0043	.010	2.5	0.12
1/2	SB12_0050	.012	2.8	0.17
9/16	SB12_0056	.012	3.5	0.19
5/8	SB12_0062	.012	3.8	0.21
3/4	SB12_0075	.012	4.9	0.27
7/8	SB12_0087	.012	5.7	0.29
1	SB12_0100	.012	6.5	0.31
1 1/8	SB12_0112	.012	7.1	0.38
1 1/4	SB12_0125	.012	7.7	0.41
1 3/8	SB12_0137	.012	8.3	0.47
1 1/2	SB12_0150	.012	8.8	0.51
1 5/8	SB12_0162	.012	9.1	0.53
1 3/4	SB12_0175	.012	9.4	0.55
1 7/8	SB12_0187	.012	9.7	0.59
2	SB12_0200	.012	9.9	0.70
3	SB15_0300	.015	12	1.40
4	SB15_0400	.015	16	1.90
5	SB15_0500	.015	19	2.20
6	SB15_0600	.015	23	2.70
7	SB15_0700	.015	27	3.10
8	SB15_0800	.015	30	3.50
10	SB15_1000	.015	38	4.40
12	SB18_1200	.018	45	6.20

*Galvanized Steel is only offered in sizes 3 inch and above.

**Fractional sizes and other material guages may be available. Please consult factory.

800-221-2319 • www.hosemaster.com