

**Kuriyama of America, Inc.**

150 N MARTINGALE ROAD

SCHAUMBURG, IL 60173-5335 USA

Phone: (847) 755-0360**Toll-Free FAX:** (800) 800-0320**International FAX:** (847) 885-0996 **Email:** sales@kuriyama.com**221 Series Linear Low Density Industrial Grade Polyethylene Tubing**

LLDPE Industrial Grade Colored Tubing for General Industrial applications.

**1**

<u>Series No.</u>	<u>Size Code</u>	<u>Nominal OD</u>	<u>Nominal ID</u>	<u>Nominal Wall</u>	<u>Max. Working Pressure at 70°F (20°C)</u>	<u>Max. Working Pressure at 122°F (50°C)</u>	<u>Standard Length</u>	<u>Pkg.</u>	<u>Approx. Wgt. Per Pkg.</u>
<u>221-0440X2K</u>	0440	1/4 in 6.4 mm	0.170 in 4.3 mm	0.040 in 1.0 mm	140 psi	60 psi	2000 ft	Spool	22 lb
<u>221-0462x2K</u>	0462	1/4 in 6.4 mm	0.125 in 3.1 mm	0.062 in 1.6 mm	150 psi	75 psi	2000 ft	Spool	30 lb
<u>221-0562X15C</u>	0562	5/16 in 7.9 mm	0.188 in 4.8 mm	0.062 in 1.6 mm	150 psi	75 psi	1500 ft	Spool	30 lb
<u>221-0662X500</u>	0662	3/8 in 9.5 mm	0.250 in 6.4 mm	0.062 in 1.6 mm	125 psi	50 psi	500 ft	Spool	13 lb

Series No.	Size Code	Nominal OD	Nominal ID	Nominal Wall	Max. Working Pressure at 70°F (20°C)	Max. Working Pressure at 122°F (50°C)	Standard Length	Pkg.	Approx. Wgt. Per Pkg.
<u>221-0662X1K</u>	0662	3/8 in 9.5 mm	0.250 in 6.4 mm	0.062 in 1.6 mm	125 psi	50 psi	1000 ft	Spool	25 lb
<u>221-0862X500</u>	0862	1/2 in 12.7 mm	0.375 in 9.5 mm	0.062 in 1.6 mm	100 psi	35 psi	500 ft	Spool	18 lb
<u>221-1062x500</u>	1062	5/8 in 15.9 mm	0.500 in 12.7 mm	0.062 in 1.6 mm	75 psi	25 psi	500 ft	Coil	23 lb