


High Pressure



H6008

Bulldog Yellow Jack



Application

- Power operated drills, boring, and mining equipment
- Provide power to air-operated equipment

Markets

- Oil and gas exploration
- Metal working
- Construction
- Mining

Construction

Tube Vinyl nitrile (RMA Class A)

Reinforcement

0.50" – 1.25" 1-wire braid
1.50" – 3.00" 2-wire braid
4.00" 3-wire braid

Cover Pin-pricked neoprene

Color Yellow

Certification

MSHA IC-46/8
RMA Class A

Operating temperature

-40°C to +93°C
(-40°F to +200°F)

Packaging

50, 100, 150 ft

Order Fulfillment

Made to Stock

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
H600816-100	25.4	1.00	39.3	1.55	69.0	1000	280	4000	1.27	0.85	30.5	100
H600820-100	31.8	1.25	47.7	1.88	45.0	650	182	2600	1.87	1.25	30.5	100
H600824-100	38.1	1.50	55.6	2.19	42.0	600	168	2400	2.49	1.66	30.5	100
H600832-100	50.8	2.00	69.0	2.72	42.0	600	168	2400	3.09	2.06	30.5	100
H600840-100	63.5	2.50	81.7	3.22	28.0	400	112	1600	3.66	2.44	30.5	100
H600848-100	76.2	3.00	96.0	3.78	28.0	400	112	1600	4.15	2.77	30.5	100

Type of couplings

- Danfoss "Z" series
- Danfoss TTC series
- Boss
- Ground joint
- Air hammer
- Air King
- Danfoss Quick disconnect

Contact coupling manufacturer for attachment procedure and other coupling recommendations