


Sandblast



H0034

Concord Sandblast



Application

- Conveys sand or shot for cleaning purposes
- Conveys sand from sandblast equipment to clean steel or concrete before painting or sealing

Markets

- Construction
- Metal working
- Ship building

Construction

Tube Synthetic rubber

Reinforcement

4-ply textile

Cover Synthetic rubber

Color Black

Abrasion loss value acc. DIN53516 $\leq 60\text{mm}^3$

Operating temperature

-40°C to +66°C
(-40°F to +150°F)

Packaging

100 ft

Order Fulfillment

Made to Stock
Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
H003408-100	12.7	0.50	27.0	1.06	10.5	150	41	600	60	2.36	0.73	0.49	30.5	100
H003412-100	19.0	0.75	38.0	1.50	10.5	150	41	600	80	3.15	1.05	0.71	30.5	100
H003416-100	25.4	1.00	47.8	1.87	10.5	150	41	600	115	4.53	1.56	1.05	30.5	100
H003420-100	31.8	1.25	54.8	2.16	8.5	125	35	500	135	5.31	1.90	1.28	30.5	100
H003424-100	38.1	1.50	60.0	2.36	7.0	100	28	400	175	6.89	2.03	1.36	30.5	100
H003432-100	50.8	2.00	73.0	2.87	7.0	100	28	400	310	12.2	2.47	1.70	30.5	100

Type of couplings

- Sandblast couplings that attach to the O.D. of hose

Contact coupling manufacturer for attachment procedure and other coupling recommendations