

Vacuum cleaner hose, antistatic $<10^{11}$ Ohm

Application

- flexible hose/ ducting for gases and for dust, powder, fibers
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- swimming pool cleaning
- scrubber, floor cleaning machine

Properties

- light weight
- highly flexible

- highly flexible
- crush resistant
- floatable
- good resistance to alkalis and acids
- surface resistance $<10^{11}$
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dusts (Zone 22 inside), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in Zone 0 (gases)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

Design

- EVA design
- self-supporting profile design
- open profile geometry
- wall: EVA

Delivery variants

- further diameters and lengths available on request
- black (standard)

I.D.	outer Ø	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
- / 20	1.055	14.765	1.654	0.087	-	30	373-0020-1002
1 / 25	1.268	14.765	2.126	0.101	30	-	373-0025-1002
- / 30	1.496	14.765	2.441	0.134	-	30	373-0030-1002
1,25 / 32	1.591	14.765	2.598	0.161	30	-	373-0032-1002
1,36 / 35	1.724	14.765	2.795	0.175	30	-	373-0035-1002
1,5 / 38	1.858	14.765	2.913	0.208	30	-	373-0038-1002
- / 40	1.945	14.765	3.150	0.215	30	-	373-0040-1002
1,75 / 44-45	2.165	14.765	3.504	0.249	30	-	373-0045-1002
2 / 50-51	2.378	14.765	3.819	0.296	30	-	373-0050-1002
2,36 / 60	2.835	14.765	4.449	0.450	30	-	373-0060-1002

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.


Accessories



CONNECT 227



CLAMP 208



CONNECT 228

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.