



**Kuriyama of America, Inc.**  
 150 N MARTINGALE ROAD  
 SCHAUMBURG, IL 60173-5335 USA  
**Phone:** (847) 755-0360  
**Toll-Free FAX:** (800) 800-0320  
**International FAX:** (847) 885-0996 **Email:** [sales@kuriyama.com](mailto:sales@kuriyama.com)

### Series HS1234 Tundra-Air® Low Temperature PVC Air Hose

High Grade Low Temperature Air Hose Assemblies (with Rubber Bend Restrictors)  
 1/4" and 3/8" sizes only.



1

| <u>Item #</u>        | <u>Standard Stock Colors</u> | <u>Size Code</u> | <u>Nominal I.D.</u> | <u>Nominal O.D.</u> | <u>Maximum Working Pressure at 70°F (20°C)</u> | <u>Maximum Working Pressure at 122°F (50°C)</u> | <u>Assembled Lengths</u> | <u>Approx. Wt. Per Pkg.</u> |
|----------------------|------------------------------|------------------|---------------------|---------------------|------------------------------------------------|-------------------------------------------------|--------------------------|-----------------------------|
| <u>HS1234-04X25</u>  | Red                          | 04               | 1/4 in<br>6.5 mm    | 0.500 in<br>12.7 mm | 300 psi                                        | 160 psi                                         | 25 ft                    | 2.0 lb                      |
| <u>HS1234-04X50</u>  | Red                          | 04               | 1/4 in<br>6.5 mm    | 0.500 in<br>12.7 mm | 300 psi                                        | 160 psi                                         | 50 ft                    | 4.0 lb                      |
| <u>HS1234-04X100</u> | Red                          | 04               | 1/4 in<br>6.5 mm    | 0.500 in<br>12.7 mm | 300 psi                                        | 160 psi                                         | 100 ft                   | 7.8 lb                      |
| <u>HS1234-06X25</u>  | Red                          | 06               | 3/8 in<br>9.5 mm    | 0.625 in<br>15.9 mm | 300 psi                                        | 160 psi                                         | 25 ft                    | 2.8 lb                      |

| <u>Item #</u>             | <u>Standard<br/>Stock<br/>Colors</u> | <u>Size<br/>Code</u> | <u>Nominal<br/>I.D.</u> | <u>Nominal<br/>O.D.</u> | <u>Maximum<br/>Working<br/>Pressure<br/>at 70°F<br/>(20°C)</u> | <u>Maximum<br/>Working<br/>Pressure<br/>at 122°F<br/>(50°C)</u> | <u>Assembled<br/>Lengths</u> | <u>Approx.<br/>Wt. Per<br/>Pkg.</u> |
|---------------------------|--------------------------------------|----------------------|-------------------------|-------------------------|----------------------------------------------------------------|-----------------------------------------------------------------|------------------------------|-------------------------------------|
| <u>HS1234-06X50</u>       | Red                                  | 06                   | 3/8 in<br>9.5 mm        | 0.625 in<br>15.9 mm     | 300 psi                                                        | 160 psi                                                         | 50 ft                        | 5.5 lb                              |
| <u>HS1234-<br/>06X100</u> | Red                                  | 06                   | 3/8 in<br>9.5 mm        | 0.625 in<br>15.9 mm     | 300 psi                                                        | 160 psi                                                         | 100 ft                       | 10.7 lb                             |
| <u>HS1234-08X25</u>       | Red                                  | 08                   | 1/2 in<br>12.7 mm       | 0.781 in<br>19.8 mm     | 300 psi                                                        | 160 psi                                                         | 25 ft                        | 4.1 lb                              |
| <u>HS1234-08X50</u>       | Red                                  | 08                   | 1/2 in<br>12.7 mm       | 0.781 in<br>19.8 mm     | 300 psi                                                        | 160 psi                                                         | 50 ft                        | 8.1 lb                              |
| <u>HS1234-<br/>08X100</u> | Red                                  | 08                   | 1/2 in<br>12.7 mm       | 0.781 in<br>19.8 mm     | 300 psi                                                        | 160 psi                                                         | 100 ft                       | 16.0 lb                             |