



Kuriyama of America, Inc.
 150 N MARTINGALE ROAD
 SCHAUMBURG, IL 60173-5335 USA
Phone: (847) 755-0360
Toll-Free FAX: (800) 800-0320
International FAX: (847) 885-0996 **Email:** sales@kuriyama.com

PNEU-THANE™ Series HS5090 Lightweight Reinforced Polyurethane Pneumatic Air Tool Hose Assemblies (with Rubber Bend Restrictors)

Lightweight Reinforced Polyurethane Pneumatic Air Tool Hose Assemblies (with Rubber Bend Restrictors).



1

<u>Item #</u>	<u>Standard Stock Colors</u>	<u>Size Code</u>	<u>Nominal ID</u>	<u>Nominal OD</u>	<u>Maximum Working Pressure at 122°F (50°C)</u>	<u>Maximum Working Pressure at 70°F (20°C)</u>	<u>Assembled Lengths</u>	<u>Approx. Wt. Per Pkg.</u>
<u>HS5090-04X25</u>	Aqua Tint	04	1/4 in 6.5 mm	0.395 in 10.0 mm	200 psi	250 psi	25 ft	1 lb
<u>HS5090-04X50</u>	Aqua Tint	04	1/4 in 6.5 mm	0.395 in 10.0 mm	200 psi	250 psi	50 ft	2.0 lb
<u>HS5090-04X100</u>	Aqua Tint	04	1/4 in 6.5 mm	0.395 in 10.0 mm	200 psi	250 psi	100 ft	4.0 lb

<u>Item #</u>	<u>Standard Stock Colors</u>	<u>Size Code</u>	<u>Nominal ID</u>	<u>Nominal OD</u>	<u>Maximum Working Pressure at 122°F (50°C).</u>	<u>Maximum Working Pressure at 70°F (20°C).</u>	<u>Assembled Lengths</u>	<u>Approx. Wt. Per Pkg.</u>
<u>HS5090-06X25</u>	Aqua Tint	06	3/8 in 9.5 mm	0.560 in 14.2 mm	200 psi	250 psi	25 ft	1.5 lb
<u>HS5090-06X50</u>	Aqua Tint	06	3/8 in 9.5 mm	0.560 in 14.2 mm	200 psi	250 psi	50 ft	3 lb
<u>HS5090- 06X100</u>	Aqua Tint	06	3/8 in 9.5 mm	0.560 in 14.2 mm	200 psi	250 psi	100 ft	6.0 lb