



Kuriyama of America, Inc.
 150 N MARTINGALE ROAD
 SCHAUMBURG, IL 60173-5335 USA
Phone: (847) 755-0360
Toll-Free FAX: (800) 800-0320
International FAX: (847) 885-0996 **Email:** sales@kuriyama.com

Series HSC2960 Polyurethane Self-Store Reinforced Hose Assembly



1

<u>Item #</u>	<u>Size Code x Length</u>	<u>Nominal ID</u>	<u>Nominal OD</u>	<u>Maximum Working Pressure at 70°F (20°C)</u>	<u>Maximum Working Pressure at 122°F (50°C)</u>	<u>Working Length</u>	<u>Coil O.D.</u>	<u>Standard Package</u>	<u>Approx. Wt. per Pkg.</u>
<u>HSC2960-04X15</u>	04 x 15	1/4 in 6.5 mm	0.395 in 9.5 mm	225 psi	125 psi	12 ft	2 in	10	6.5 lb
<u>HSC2960-04X25</u>	04 x 25	1/4 in 6.5 mm	0.395 in 9.5 mm	225 psi	125 psi	20 ft	2 in	10	10 lb
<u>HSC2960-04X50</u>	04 x 50	1/4 in 6.5 mm	0.395 in 9.5 mm	225 psi	125 psi	40 ft	2 in	1	2.0 lb
<u>HSC2960-06X15</u>	06 x 15	3/8 in 9.5 mm	0.570 in 14.5 mm	225 psi	125 psi	12 ft	3 in	5	7.0 lb
<u>HSC2960-06X25</u>	06 x 25	3/8 in 9.5 mm	0.570 in 14.5 mm	225 psi	125 psi	20 ft	3 in	5	11 lb

<u>Item #</u>	<u>Size Code x Length</u>	<u>Nominal ID</u>	<u>Nominal OD</u>	<u>Maximum Working Pressure at 70°F (20°C)</u>	<u>Maximum Working Pressure at 122°F (50°C)</u>	<u>Working Length</u>	<u>Coil O.D.</u>	<u>Standard Package</u>	<u>Approx. Wt. per Pkg.</u>
<u>HSC2960- 06X50</u>	06 x 50	3/8 in 9.5 mm	0.570 in 14.5 mm	225 psi	125 psi	40 ft	3 in	1	4.0 lb