



Kuriyama of America, Inc.
 150 N MARTINGALE ROAD
 SCHAUMBURG, IL 60173-5335 USA
Phone: (847) 755-0360
Toll-Free FAX: (800) 800-0320
International FAX: (847) 885-0996 **Email:** sales@kuriyama.com

Series K3285 NSF-61 Certified Reinforced PVC Flexible Connection Hose

A Flexible, Phthalate Free Non-Contaminating NSF-61 certified hose that is ideal for use in drinking water applications.



1

<u>Series No.</u>	<u>Size Code</u>	<u>Nominal ID</u>	<u>Nominal OD</u>	<u>Max. Working Pressure at 70°F (20°C)</u>	<u>Max. Working Pressure at 150°F (66°C)</u>	<u>Standard Length</u>	<u>Approx. Wt. per Pkg.</u>
<u>K3285-05X500</u>	05	0.320 in 8.1 mm	0.485 in 12.3 mm	180 psi	125 psi	500 ft	29 lb
<u>K3285-06X500</u>	06	0.380 in 9.7 mm	0.595 in 15.1 mm	180 psi	125 psi	500 ft	46 lb
<u>K3285-08X500</u>	08	0.505 in 12.8 mm	0.740 in 18.8 mm	180 psi	125 psi	500 ft	64 lb

1