


Concrete, Plaster & Grout



EHK006

Marauder

**Application**

- For high pressure concrete pumping
- For high pressure spraying plaster, grout, sand, gypsum, and ready mixed concrete
- Light weight for hand held applications

Markets

- Construction
- Cement
- Swimming pool
- Tunnel faces
- Dams

Construction

Tube Abrasion resistant anti-static natural rubber

Reinforcement

High tensile synthetic textile and anti-static copper wire

Cover Abrasion, ozone and weather resistant pin-pricked synthetic rubber

Color Black

Certifications

Meets the requirements of ASME B30.27-2014

Abrasion loss value acc. DIN53516 $\leq 60\text{mm}^3$

Operating temperature

-40°C to +70°C
(-40°F to +158°F)

Packaging

100 ft

Order Fulfillment

Made to Stock
Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHK006-20-100	32.0	1.25	48.8	1.92	85.0	1233	178	2581	1.22	.820	30.5	100
EHK006-24-100	38.0	1.50	58.7	2.31	85.0	1233	178	2581	1.81	1.21	30.5	100
EHK006-32-100	50.8	2.00	72.0	2.83	85.0	1233	178	2581	2.40	1.61	30.5	100
EHK006-40-100	63.5	2.50	86.3	3.40	85.0	1233	178	2581	3.01	2.02	30.5	100
EHK006-48-100	76.2	3.00	96.6	3.92	85.0	1233	178	2581	3.65	2.45	30.5	100
EHK006-64-100	101.6	4.00	126.0	4.92	85.0	1233	178	2581	4.74	3.18	30.5	100
EHK006-80-100	127.0	5.00	153.5	6.04	85.0	1233	178	2581	6.38	4.29	30.5	100

Type of couplings

- Victaulic male NPT

Contact coupling manufacturer for attachment procedure and other coupling recommendations