

MORTAR



Mandals **Mortar** is a light weight, safe & easy to use concrete boom hose from Mandals AS.

The hose answers a need in the market for an easy to handle concrete placement hose.

It is ideal for ICF forms as well as tall walls, and columns where space is minimal.

The Lay-Flat design allows improved flow control and lower placement rates compared to conventional concrete discharge hoses.

Mandals Mortar conforms with or exceeds strictly safety regulation such as the North American ASME B30.27 2009

INDUSTRIES CONSTRUCTION

FEATURES

- Light weight, safe and easy to use concrete boom hose
- Ideal for ICF forms as well as tall walls, and columns with limited space.
- Improved flow control and placement rates compared to conventional concrete discharge hoses.
- Excellent abrasion resistance

DESIGN

- Mandals Mortar conform with or exceed strict safety regulation such as North America ASME B30.27 2009
- Extruded through a circular woven jacket
- Very strong bond between cover and lining and encapsulates the reinforcement.

ADVANTAGE

- 1/3 lighter than traditional Flexible boom hose
- Safer operations and excellent maneuverability
- Outstanding wearing resistance
- Custom various lengths
- Ease to pour in high areas
- Bright color for visibility and safety
- Simple maintenance and clearing operation
- Coils up for storage and transportation

TECHNICAL DATA

INNER DIAMETER		WALL THICKNESS		WEIGHT		BURST PRESSURE		TENSILE STRENGTH	
Inch	mm	Inch	mm	Lbs / ft	Kg / m	Psi	Bar	X1000 kbs	Tons
4	110,5 + 2,0	0,17	4,2	1,16	1,73	2500	172	178	80
5	135,5 + 2,0	0,18	4,5	1,64	2,45	2500	172	218	98

MORTAR

Mandals Mortar is made from extruded thermoplastic polyether based polyurethane (TPU) with excellent wear & tear characteristics.

The circular woven reinforcement is made from an extra strong yarn.

The extrusion through the weave

production method gives a very strong bond between cover and lining, and encapsulates the reinforcement.

The heavily reinforced weave ensure minimum extension in length and minimum "snaking" or bending of the hose.



Contact
sales@mandals.com
(47) 38 27 24 00
Nordre Banegate 26, 4515Mandal, Norway

mandals
SINCE 1775