




T254AA 150 PSI SBR Water Discharge Hose

Applications:

Water discharge hose for construction and irrigation.

Cover:

Black SBR – abrasion and ozone-resistant.

Reinforcement:

High tensile textile cords.

Tube:

Black SBR.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Standard Length:

100 feet: 1 1/2" through 8"

50 feet: 8"

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T254AA150	1 1/2	38	1.89	48	150	0.66
T254AA200	2	51	2.40	61	150	0.87
T254AA300	3	76	3.46	88	150	1.54
T254AA400	4	102	4.49	114	150	2.08
T254AA600	6	152	6.54	166	150	3.13
T254AA800	8	203	8.62	219	150	4.64

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.